







# **PP10-C**

SPECIFICATION & TECHNICAL INFORMATION SHEET



The PP10 with Channel is designed to support electrical conduit and condensate drain lines up to 3-1/2" OD, not exceeding 16" in height. The support is designed for installation without roof penetrations, flashings, or damage to the roofing material. The support can be used on virtually any roofing system from flat roofs to roofs sloped up to 2 in 12. The supports should be spaced according to the specifications. Seismic and High-Wind applications are available for the system.

## **INSTALLATION PROCEDURE:**

#### **New Pipe**

- 1 Layout isolation pads, (provided by contractor), according to the design and layout.
- 2 Layout PP10-C supports per spacing specifications or PHP layout.
- **3** Run pipe on channel.
- 4 Clamp down with channel clamp, (provided by contractor).
- Adjust channel until height and weight of system is evenly distributed.

# Retro-fit

- Lift piping, (enough to remove existing support).
- 2 Clean area where new support is to be placed.
- **3** Place ISO pad, (provided by contractor).
- 4 Place PP10-C support on pad.
- 5 Lower pipe onto channel.
- 6 Clamp down with Channel clamp, (provided by contractor)
- **7** Adjust channel until height and weight of system is evenly distributed.



#### STORAGE:

Store in the original, unopened containers, under cover, until needed for installation.

## **LEED INFORMATION:**

Frame/Steel

Post Consumer Recycled Content: 0% Post Industrial Recycled Content: 25%

#### **BASE MATERIAL:**

Post Consumer Recycled Content: 80% Post Industrial Recycled Content: 20% Manufacturing Location: Houston, TX

#### **PRODUCT DATA:**

Property:	Minimum	Performance:
Base:		

Size: 10" x 16" x 3" Base Weight: 5-1/2 lbs

Base Material: Injection molded high density/high impact

polypropylene with

UV-inhibitors and Antioxidants

Base Color: Black

Base Density: 55.8 lb/cu ft (894 kg/cu m)

#### Rod Type:

Diameter: 1/2" Length: 4" - 16"

Finish: Hot Dip Galvanized or 304 Stainless Steel

#### Carbon Steel and 304 Stainless Steel Framing:

Channel Type: 13/16 x 12"

Roll-formed 3-sided tubular Form: shape, perforated with 2" slots

at 2" centers on one side

Thickness: 12 gauge

Carbon Steel Finish: Hot dip galvanized per ASTM A 123

Stainless Steel Finish: Mill Finish

## **Hardware:**

Nuts and Washers: Hot Dip Galvanized

or 304 Stainless Steel